

DECLARATION OF PERFORMANCE

No. 00001EXPRIVINT

1. Unique identification code of the product-type:
Number of type, batch, series or any other element to identify the construction product: **Dry pressed ceramic tiles, with water absorption $E_b > 10\%$**
2. Expected use: **for indoor walls**
3. Manufacturer **EXPORTCERAM FIDEURO SPA
VIA LA PIANA 2
41045 MONTEFIORINO MO**
4. AVCP system(s) **SYSTEM 4**
5. Name and identification number of the notified laboratory, if concerned **NOT APPLICABLE**
6. Declared performance:

MAIN FEATURES	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Fire reaction	A1	EN 14411:2012
Release of harmful substances, for		
- Cadmium	NPD	
- Lead	NPD	
Breaking stress	Thickness ≥ 7.5 mm > 600 N Thickness < 7.5 mm < 200 N	
Bending strength or module of rupture	Thickness ≥ 7.5 mm > 12 N/mm ² Thickness < 7.5 mm > 15 N/mm ²	
Adhesion resistance Cement adhesives,	NPD	
Resistant to sudden temperature changes	Pass	
Durability: - Indoor use	Pass	

7. The performance of the product as per points 1 and 2 complies with the performance stated at point 6.


8. This declaration of performance is released under the sole responsibility of the manufacturer as per point 3.

Signed on name and behalf of:

CARLO TRALDI, MANAGER
(name and title)

Montefiorino, 10/06/2024
(Place and date of release)

EXPORTCERAM FIDEURO S.P.A


(signature)